



Product Information NS-A.12.09

Lube-oil industry • Industrie Lubrifiant

Smeermiddelenindustrie • Schmiermittelindustrie

DE OLIEBRON LUBRICATION(GD) CO.,LTD

TEL: +86 4008801150 Internet: http://www.deoliebron.com E-mail: info@deoliebron.com

4T Motorcycle FS 10W50

Description

A new generation full-synthetic engine oil for four-stroke motorcycles formulated with synthetic base oils combined with special developed balanced additives to achieve the following properties:

- a high and stable viscosity index
- optimal friction characteristics
- a very strong protection against wear, corrosion and foaming
- a very good detergency and dispersion

Application

This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.

Specifications

Performance level:

API SN JASO MA2 JASO MA

Typicals

Density at 20 °C, kg/l	0,861
Viscosity -30 °C, mPa.s	6499
Viscosity 40 °C, mm ² /s	122,52
Viscosity 100 °C, mm ² /s	17,95
Viscosity Index	163
Flash Point COC, °C	232
Pour Point, °C	-39
Total Base Number, mgKOH/g	7,7
Sulphate Ash %	