



Smeermiddelenindustrie • Schmiermittelindustrie

DE OLIEBRON LUBRICATION(GD) CO.,LTD

TEL: +86 4008801150

Internet: <http://www.deoliebron.com>

E-mail: [info@deoliebron.com](mailto:info@deoliebron.com)

Lube-oil industry • Industrie Lubrifiant

### SynthTech LL-X 5W40

#### Description

A modern, Fully synthetic, universal motor oil based on special selected synthetic base oils, among others ester, with a high viscosity index and a well balanced choice of advanced

additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

#### Application

This universal, ester fortified, fuel saving synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.

#### Specifications

Performance level:

ACEA C3

API SP, API SN Plus

BMW Longlife-04

MB 229.31/229.51

VW 502.00 and 505.00

#### Typicals

Density at 20 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	6196
Viscosity 40 °C, mm <sup>2</sup> /s	89,52
Viscosity 100 °C, mm <sup>2</sup> /s	14,54
Viscosity Index	169
Flash Point COC, °C	234
Pour Point, °C	-42
Total Base Number, mgKOH/g	7,05
Sulphate Ash, %	0,75