De Oliebron



Product Information NS-A.12.17

Lube-oil industry • Industrie Lubrifiant

Smeermiddelenindustrie • Schmiermittelindustrie DE OLIEBRON LUBRICATION(GD) CO.,LTD TEL: +86 4008801150 Internet: http://www.deoliebron.com E-mail: info@deoliebron.com

Г

4T Motorcycle Synthetic 10W30

Description	 A new generation synthetic engine oil for four-stroke motorcycles formulated with synthetic base oils combined with special developed balanced additives to achieve the following properties: a high and stable viscosity index optimal friction characteristics a very strong protection against wear, corrosion and foaming a very good detergency and dispersion
Application	This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.
Specifications	Performance level: API SN JASO MA2 JASO MA
Typicals	Density at 15 °C, kg/l 0,8468 Viscosity -25 °C, mPa.s 3770 Viscosity 40 °C, mm²/s 11,72 Viscosity Index 157 Flash Point COC, °C 257 Pour Point, °C -42 Total Base Number, mgKOH/g 6,45
05/01/2019	The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier applications, to make the final product-choice in consultation with the supplier. Due to continual product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website.